



Engine Technical Data

Unit	3TNV84T-KSA	3TNV84T-KSA2	3TNV84T-KSA3
------	-------------	--------------	--------------

General Data

Number of Cylinders	-	3	
Engine Type	-	Inline, Water-Cooled, 4 Stroke Diesel	
Bore x Stroke	mm x mm	84 x 90	
Total Displacement	cc	1496	
Combustion type	-	Direct Injection	
Aspiration	-	Turbocharged Aspiration	
Valves per Cylinder	-	2	
Compression ratio	-	19.0	
Firing Order	-	1-3-2	

Performance Data

Net Intermittent Power	HP [kW] / rpm]	38.9 [29.0]/2800	
Net Continuous Power	HP [kW] / rpm]	--	
Net Max Torque	ft-lb [Nm]/rpm	88.1 [119.5]/1500	
Low Idle Speed	rpm	1000+/-25	
High Idle Speed	rpm	2995+/-25	
BMEP, Net Power	Psi [kPa]	121 [834]	
BMEP, Cont. Power	Psi [kPa]	--	

Physical Data

Direction of rotation	-	Counter Clockwise (view from flywheel)		
Length - Inches	Inches [mm]	24.69 [627]	22.95 [583]	22.64 [575]
Width - Inches	Inches [mm]	20.20 [513]		
Height - Inches	Inches [mm]	27.44 [697]		
Dry Weight	lbs [kg]	386 [175]	362 [164]	346 [157]
Center of Gravity:	-			
From Rear Face of Block	Inches [mm]	5.24 [133]		
From Crankshaft to Exhaust Side	Inches [mm]	0.43 [11]		
Above Crankshaft	Inches [mm]	3.62 [92]		

PTO System

Flywheel	-	SAE #5	Semi SAE #5	Semi SAE #5
Flywheel Housing	-	SAE #5 (Depth 124)	Semi SAE #5 (Depth 80)	Back Plate
Gear Case	-	with SAE Hydraulic Pump Flange		

Lubrication System

Inclination, Continuous	degrees	30	
Inclination, 3 minutes Max.	degrees	35	
Oil Pan Style	-	Deep	
Lubrication Oil Filter Type	-	Paper Element	
Temperature Limit (main oil pressure passage)	°F [°C]	248 [120]	
Nominal Oil Pressure	psi [kgf/cm2]	64 [4.5]	
Oil Capacity, Effective	Liters	2.8	
Total System Capacity	Liters	6.7	
Oil Change Interval, Hours	hr	250 (50, initial)	
Recommended Oil Type	API	CD, CF or higher grade	

Engine Technical Data

Unit	3TNV84T-KSA	3TNV84T-KSA2	3TNV84T-KSA3
------	-------------	--------------	--------------

Cooling System

Fan Type	-	Puller
Fan Diameter	Inches [mm]	14.17 [360]
Number of Blades	-	7
Fan Pulley Diameter	Inches [mm]	4.33 [110]
Crank Pulley Diameter	Inches [mm]	4.33 [110]
Fan Spacer Thickness - Inches [mm]	Inches [mm]	0.98 [25]
Max. Coolant Temp.	°F [°C]	221 [105]
Thermostat Starts Opening	°F [°C]	160±2.7 [71 ± 1.5]
Thermostat Fully Open	°F [°C]	185 [85]
Coolant Capacity (Engine)	Liters	2
Coolant Flow (C. W. Pump)	Liters / min	52.6
Heat Rejection at Rated Power	BTU/hr [kcal/hr]	73800 [18600]

Fuel System

Fuel Filter Type	-	Paper Element
Fuel Injection Pump Type	-	Distributor Type
Water Separator (Standard)	-	Mesh size: 100-mesh/inch, water reservoir 150 cc
Max. Suction Head (Fuel pickup to Injection pump)	Inches [mm]	40 [1000]
Fuel Feed Pump Type	-	Electrical
Fuel Flow (Feed pump)	Liters / hr	60
Max. Allowable Fuel Temperature	° F [°C]	176 [80] Fuel Injection In
Required Separation Distance Between Pickup & Return	Inches [mm]	min. 4 [100]
Fuel Consumption at Net Inter. Power	lb/hp-hr [g/kW-hr]	0.41 [252]

Intake System

Max. Air Intake Restriction, initial	Inch Aq [kPa]	11.8 [2.9]
Max. Air Intake Restriction, replace element	Inch Aq [kPa]	25 [6.2]
Crankcase Ventilation Type	-	Opened
Engine Air Flow (For sizing air cleaner)	ft ³ / min. [m ³ /min]	163 [4.6]@2800 rpm

Exhaust System

Max. Allowable Back Pressure, initial	Inch Aq [kPa]	19.7 [4.9]
Max. Allowable Back Pressure, cleaning	Inch Aq [kPa]	23.6 [5.9]
Exhaust Air Flow @ Max. Power Exhaust Temp.	ft ³ / min. [m ³ /min]	313 [8.9]
Exhaust Temperature at Max. Power	° F [°C]	1202 [650]
Exhaust Temperature at Max. Torque	° F [°C]	1035 [557]

Electrical System

System Voltage	Volts	12 V
Electric Stop Device	-	Stop Solenoid
Alternator	-	12V-40A
Starting Aid Device	-	Air Heater, 12V 400W
Standard pre-heat time	Seconds	15
Engine Block Heater Port	-	Exhaust Side
Starting Motor Type	-	Reduction
Starting Motor Power	kW	1.7
Maximum Starter Cable Resistance	Ohm (Ω)	0.05
Maximum Battery Cable Resistance	Ohm (Ω)	0.002

Revision: 2

History:

Revision 2, 07/19/2004

Rearranged table

Corrected the Exhaust Air Flow @32 oF(0 oC) to Max. Power Exhaust Temp.

Manager	S. Manager	Written by

Date: October 29, 2003

Doc. No.: YAE-Spec-03-0030 Page: 2/2